

	TARALAY ROMA 柏莱罗马		
	ROMA 罗马		
DESCRIPTION 规格			
Total thickness 总厚度	ISO 24346 (EN 428)	mm	2.6
Wearlayer thickness 耐磨层厚度	ISO 24340 (EN 429)	mm	0.7
Weight 重量	ISO 23997 (EN 430)	g/m ²	3800
Width of sheet 卷宽	ISO 24341 (EN 426)	cm	200
Length of sheet 卷长	ISO 24341 (EN 426)	lm	15
CLASSIFICATION 类别			
Norm / Product specification 产品规范	-	-	ISO 10582 (EN 649)
European classification 产品分类	ISO 10874 (EN 685)	class	34-43
Fire rating 防火等级	EN 13501 - 1	class	Bfl-s1
	GB 8624 - 2012	class	B ₁ (B-s1, t0)
Toxic testing 有毒有害物质检测	GB 18586 - 2001	-	合格
Static electrical propensity 抗静电性	EN 1815	kV	< 2
Slip resistance wet 防湿滑性	DIN 51 130	class	R9
PERFORMANCES 性能			
Wear resistance 耐磨性	EN 660.2	mm ³	≤ 2
Wear group 耐磨等级	EN 649	group	T
Type binder content 粘合物分级	ISO 10582	type	I
Dimensional stability 尺寸稳定性	ISO 23999 (EN 434)	%	≤ 0.4
Residual indentation 残余凹陷度	ISO 24343-1 (EN 433)	mm	≤ 0.1
Castor chair test 椅子脚轮测试	ISO 4918 (EN 425)	-	OK
Thermal conductivity 热传导性	ISO 10456 (EN 12524)	W/(m.k)	0.25
Colour fastness 颜色稳定性	ISO 105 - B02	degree	≥ 6
Chemical product resistance 抗化学性	ISO 26987 (EN 423)	-	OK
Anti-bacterial and fungicidal treatment 抗菌防霉处理	-	-	Sanosol
Special maintenance treatment 特殊维护处理	-	-	Protecsole®
Anti-bacterial activity 抑菌性能 (E.coli - S.aureus - MRSA 大肠杆菌和金黄色葡萄球菌) (1)	ISO 22196	-	> 99% inhibits growth 抑菌率
ENVIRONMENT / INDOOR AIR QUALITY 环保 / 室内空气质量			
TVOC ₍₂₎ after 28 days 28天后TVOC排放量	ISO 16000 - 6	µg/m ³	< 100
Certification 证书	-	-	Floorscore®
CE MARKING 标识			
	EN 14041	 防滑  供地下暖气设备使用  抗静电  防火	

(1) The implementation of an effective cleaning regime is the most important defence against infections. 实施有效的清洁方法是抗感染最重要的防御措施。

(2) TVOC即挥发性有机化合物总排放量

